

NATIONAL INSTITUTE OF TECHNOLOGY
KURUKSHETRA-136119

No. SEO/29/13-14

Dated: 23.01.2014

M/s Addresses
As per list attached

Sub: INVITATION OF QUOTATIONS FOR PROVIDING & FIXING ALUMINIUM PARTITIONING, FALSE CEILING AND TEXTURE PAINT ETC.

1. You are invited to submit your most competitive quotation for the following goods:

- | Sr.No. | Brief Description & Specifications of Goods | Quantity |
|--------|---|------------------------|
| 1. | PROVIDING & FIXING ALUMINIUM PARTITIONING, FALSE CEILING AND TEXTURE PAINT ETC. | (As per list attached) |
2. Necessary literature of the goods may please be sent to facilitate to take decision.
 3. All duties taxes and other levies payable by the Institute shall be included in the total price. This Institute does not issue Form C or D.
 4. Payment is normally made by Cheque drawn on State Bank of India within 30 days after receipt of material in good condition and according to specifications.
 14. The supplier shall deposit Earnest Money alongwith the Quotation amounting to Rs.22000/-in shape of Accounts Payee Demand Draft, Fixed Deposit Receipt, Bankers Cheque or Bank Guarantee from any commercial Bank in favour of the Director, National Institute of Technology, Kurukshetra. The Quotations without Earnest Money shall be rejected, the EMD will remain valid for a period of 45 days beyond the final validity period of quotation.
 15. Performance Security @ 05% of the total value of the equipment may be furnished in shape of Demand Draft, Fixed Deposit Receipt or Bank Guarantee from any Commercial Bank in favour of the Director, NIT Kurukshetra valid upto 60 days after the date of completion of warranty period of one year.
 16. The items must be supplied within delivery period or delivery period extended by the Institute on the request of the supplier on genuine grounds otherwise the penalty for delayed period @ 0.5% of the amount shall be charged for every week or part thereof and the maximum 10%.
 8. The goods are not required exclusively for Research Purpose. The Duties are payable by the Institute.
 9. The quotation should remain valid for a period not less than 60 days from the date of submission.
 10. The right of accepting or rejecting any quotation and to cancel the bidding process and reject all quotations without assigning any reason is reserved with the Institute.
 11. The due date for receipt of quotation is 11.02.2014 and will be opened on next working day. Please quote on the top of the envelope our Ref. No. and due date of opening.

[Signature]
Asstt. Registrar (Stores)
23/1/14

NATIONAL INSTITUTE OF TECHNOLOGY
KURUKSHETRA – 136 119

Subject: Revised Cost estimate as per revised plan for the provision of aluminium partitioning, false ceiling and textured paint etc. in the space recently allotted to Training and Placement in the old administrative building, NIT Kurukshetra.

Sr No.	Code No.	Description	Quantity	Unit
1	21.1	Providing and fixing aluminium work for doors, windows, ventilations and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, aluminium snap beading for glazing/paneling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the direction of Engineer-in-charge (Glazing, paneling and dash fasteners to be paid for separately):		
	21.1.1	For fixed portion		
	21.1.1.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	590.00	Kg.
2	21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/neoprene gasket required (Fittings shall be paid for separately)		
	21.1.2.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	215.00	Kg.
3	21.2	Providing and fixing 12 mm thick pre-laminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12623 Grade I Type II, in paneling fixed in aluminium doors, windows shutters and partition frames with C.P. brass/stainless steel screws etc. complete as per architectural drawings and direction of engineer-in-charge.		
	21.2.2	Pre-laminated particle board with decorative lamination on both sides.	170.00	
4	21.3*	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge (Cost of aluminium snap beading shall be paid in basic item):		
	21.3.2	With float glass panes of 5.50 mm thickness	15.00	Sqm.
5	12.53	Providing and Fixing 15 mm thick densified regular edged eco friendly light weight calcium silicate false ceiling tiles of approved texture spintone/cosmos / Hexa or equivalent of size 595 x 595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanising @ 120 grams per sqm including both side) consisting of main 'T' runner suitably spaced at joints to get required length and of size 24x38 mm made from 0.33 mm thick (minimum) sheet, spaced 1200 mm centre to centre, and cross 'T' of size 24x28 mm made out of 0.33 mm (Minimum) sheet, 1200 mm long spaced between main 'T' at 600 mm centre to centre to form a grid of 1200x600 mm and secondary cross 'T' of length 600 mm and size 24 x28 mm made of 0.33 mm thick (Minimum) sheet to be inter locked at middle of the 1200x 600 mm panel to form grid of size 600x600 mm, resting on periphery walls /partitions on a Perimeter wall angle pre-coated steel of size (24x24X300) mm made of 0.40 mm thick (minimum) sheet with the help of rowl plugs at 450 mm centre to centre with 25 mm long dry wall screws @ 230 mm interval Note :- Only calcium silicate false ceiling area will be measured from wall to wall. No deduction shall be made for exposed frames/opening (cut outs) having area less than 0.30 sqm. The calcium silicate ceiling tile shall have NRC value of 0.50 (Minimum), light reflection > 85%, non - combustible as per B.S.		

		476 part IV, 100% humidity resistance and also having thermal conductivity <0.043 w/m 0 KC. and laying 15 mm thick densified edges calcium silicate ceiling tiles of approved texture (Spintone / Cosmos/hexa) in the grid, including, cutting/ making opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc, wherever required. Main 'T' runners to be suspended from ceiling using G.I. slotted cleats of size 25x35x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm G.I. adjustable rods with galvanized steel level clips of size 85 x 30 x 0.8 mm, spaced at 1200 mm centre to centre along main 'T', bottom exposed with 24 mm of all T-sections shall be pre-painted with polyester baked paint, for all heights, as per specifications, drawings and as directed by engineer-in-charge. Note - Only calcium silicate false ceiling area will be measured from wall to wall. No deduction shall be made for exposed frames/opening (cut outs) having area less than 0.30 sqm. The calcium silicate ceiling tile shall have NRC value of 0.50 (Minimum), light reflection > 85%, non-combustible as per B.S. 476 part IV, 100% humidity resistance and also having thermal conductivity <0.043 w/m 0 KC.	244.52	Sqm.
R	13.45	Finishing walls with textured exterior paint of required shade :		
	13.45.1	New work (Two or more coats applied @ 3.28 ltr/10 sqm) over and including priming coat of exterior primer applied @ 2.20kg/10.sqm	306.23	Sqm.

final
23/12/13
J.E. (Civil)

Assistant Engineer (Civil)

[Signature]
24/12/13

Prof. IIC (E & C)

[Signature]
26/12/13

Dean (Estate)

[Signature]
30/12/13