



**Item with specification to be purchased for Mega Hostel (Boys):**

Sr. No.	Description of items	Overall Size	Qty.
1.	<p><b>SELF SERVICE HOT FOOD COUNTER.</b>            Unit top Shall be constructed 16swg stainless steel top with front turned down 2" &amp; in 1/2" Top of the unit provide hot bain marie with GN pan. Complete water inlet, outlet and electric control. Unit all sides clad with 20swg SS sheet. Unit shall be mounted (4) nos. 1-1/2" ss pipes legs with adjustable bullet feet, 18sqg. SS bottom shelf to be provided. Six Gastronorm Pans shall be used in bain marie. Four GN Pans Size: 1/1-21"x13"x6" deep for keeping Dal, Dry vegetable, Roti and Rice. Two GN Pans Size: 1/2 - 13"x10.5"x6" deep for keeping Curd and Salad. Tray Slide made by SS pipe.</p>	78"x27"+12"x34"	2
2.	<p><b>CHAPATI PLATE WITH PUFFER.</b>            Framework made of ms angle. Top made of 12mm thick ms plate with ms puffers. The verticals of the equipment are made of stainless steel and cross bracing. The unit has front panel and side covered up to 300mm. Wide beneath the top, made of 20swg stainless steel sheet. The unit is provided with "V" Shape burners and pilot burners and pilot lamps with independent needle valve controls.</p>	5'x2'x34"	2
3.	<p><b>SINGLE BURNER COOKING RANGE.</b>            Top constructed of 16swg SS sheet. Top shall be secured to ms deldedd angle frame work. Unit shall be mounted (4) no. 1-1/2" SS pipes legs with adjustable bullet feet. Unit leg shall be crossed braced with 1" SS pipe cross bracing at all sided. Unit top receive (1) no. cast iron grates with one no. burner with pilot burner. Under sides of burner shall be provided SS slide out drip tray with handle to be provided.</p>	30"x30"x24"	2
4.	<p><b>TWO BURNER COOKING RANGE</b>            Top constructed of 16swg SS sheet. Top shall be secured to ms deldedd angle frame work. Unit shall be mounted (4) no. 1-1/2" SS pipes legs with adjustable bullet feet. Unit leg shall be crossed braced with 1" SS pipe cross bracing at all sided &amp; full width bottom shelf made by ss sheet. Unit tip receive (2) nos. cast iron grates with two nos. burners with provide SS slide out drip tray with handle to be provided.</p>	60"x24"x34"	1
5.	<p><b>THREE BURNER COOKING RANGE</b>            Top constructed of 16swg SS sheet. Top shall be secured to ms deldedd angle frame work. Unit shall be mounted (4) no. 1-1/2" SS pipes legs with adjustable bullet feet. Unit leg shall be crossed braced with 1" SS pipe cross bracing at all sided &amp; full width bottom shelf made by ss sheet. Unit tip receive (3) nos. cast iron grates with three nos. burners with pilot burners. Under sides of burner shall be provide SS slide out drip tray with handle to be provided.</p>	72"x24"X34"	1
6.	<p><b>POTATO PEELER.</b>            Peeling drum made 16swg stainless steel sheet with s. steel disc revolving. Top peeling chamber &amp; disc lined with abrasive material. Lower body 20swg SS sheet on ms angle frame work fitted one HP electric motor with control switch.</p>	CAP:10 KG PER CHARGE	1
7.	<p><b>WET GRINDER TILL TING TYPE.</b>            Stainless steel body, stainless steel revolving drum, grinding stone &amp; wooden scrapper. Fitted with 2 HP electric motor &amp; gear box.</p>	CAP: 15 LTRS.	1

8.	<b>ATTA KNEADING MACHINE.</b> Cast iron body with gear operated 2 HP motor & SS drum and SS kneading arm.	CAP: 40 LTRS.	1
9.	<b>VEGETABLE CUTTING MACHINE</b> with special steel three blades	ELECTRIC	1
10.	<b>CHAPATTI MAKING MACHINE.</b> Weight of Chapati – 25 gms -45gms. Chappati thickness – 1.5mm – 2.5mm Chappati Size: 4.5” – 6.5” Colour – Light brown Appearance – soft with puffer layer LPG consumption – 1.25kg to 1.75kg/Hour LPG pressure – 5 p.s.i to 7 p.s.i Electricity Consumption – 1.15 kw <b>Tested by National Testing Laboratory</b>	Cap: 900-1000 chappati/Hour	1
11.	<b>DISH WASHER HOOD TYPE.</b> Cap: 40/24 in racks/hr. Tank Temperature 60 dc Boiler Temperature 85 dc Nominal operating Voltage 415 V (50 Hz) Total connected load 9.1/15.1 KW Fresh water requirement per cycle – 3.2L W x D x H -635x749x1420 MM. Input height 420 +/- 5 MM Rack dimensions 500 x 500 MM	Imported Winter halter make	1
12.	<b>SS EXHAUST HOOD.</b> Hood body constructed of 20swg SS sheet. All welded construction. Unit shall be provided 20”x20”x2” thick SS baffle type grease filters with handle & set at an angle of 45 deg. In full length with bottom of filters set in continuous channel smooth clean wiping grease gutter on rear sides only. Bulk head light fixture bottom of hood shall be provided ss grease drawer with handle.		
	<b>A FOR ITEM NO. 2 CHAPATI PLATE PUFFER</b>	66”x30”	1
	<b>B FOR ITEM NO. 3 SINGLE BURNER RANGE</b>	66”x36”	1
	<b>C FOR ITEM NO. 4 TWO BURNER RANGE</b>	66”x30”	1
	<b>D FOR ITEM NO. 5 THREE BURNER RANGE</b>	78”x30”	1
13.	<b>EXHAUST SYSTEM – 10000 CFM</b> Ms body exhaust Centrifugal backward curve blower having capacity 10000 CFM v-belt & pulley suitable for 3 HP electric motor.		1
14.	<b>GI DUCTING – 24swg.</b>		

**\*Note: The quotations would be evaluated for all the items together for price comparison.**